

What is claimed is:

1. A lamp bracket for cold cathode lamps adapted for using on
a connection circuit of a power cord of a cold cathode lamp
and a power supply end to connect to a circuit board,
5 comprising:
an anchor dock having a bottom seat and a cap movable
to cover said bottom seat for opening or closing; and
at least one line coupling means located between said
bottom seat and said cap and made from metal sheet for
10 connecting said power cord of said cold cathode lamp.
2. The lamp bracket for cold cathode lamps of claim 1,
wherein said cap and said bottom seat have respectively a first
latch section and a second latch section that have mating
shapes for coupling with each other to latch said cap and said
15 bottom seat.
3. The lamp bracket for cold cathode lamps of claim 1,
wherein said bottom seat has a through hole in the center for
housing an insertion leg to connect said line coupling means
and said power supply end.
- 20 4. The lamp bracket for cold cathode lamps of claim 3,
wherein said insertion leg has a distal end forming a tenon
and a notch, said tenon being latchable on said circuit board
through said through hole and retractable towards said notch
during insertion in said through hole.
- 25 5. The lamp bracket for cold cathode lamps of claim 1,

wherein said line coupling means has a lower end connecting to a metal wire which is linked to said power supply end.

6. The lamp bracket for cold cathode lamps of claim 1, wherein said line coupling means is integrated and bent to
5 form an upper coupling member and a lower coupling member, said lower coupling member being fixedly mounted onto said bottom seat of said anchor dock.

7. The lamp bracket for cold cathode lamps of claim 1, wherein said line coupling means is integrated and bent to
10 form an upper coupling member and a lower coupling member, said lower coupling member being connected to an insertion leg which is connected to said power supply end.

8. The lamp bracket for cold cathode lamps of claim 1, wherein said line coupling means includes an upper coupling
15 member fixedly located on said cap and a lower coupling member fixedly located on said bottom seat.

9. The lamp bracket for cold cathode lamps of claim 6 or 7, wherein the upper coupling member has a lead trough and said lower coupling member has a compression bump mating the
20 shape of said lead trough.

10. The lamp bracket for cold cathode lamps of claim 8, wherein said upper coupling member has a lead trough and said lower coupling member has a compression bump mating the shape of said lead trough.

25 11. The lamp bracket for cold cathode lamps of claim 1,

wherein said anchor dock has a connecting section for linking said cap and said bottom seat.

12. The lamp bracket for cold cathode lamps of claim 11, wherein said connecting section is a hinge.

- 5 13. The lamp bracket for cold cathode lamps of claim 11, wherein said cap, said bottom seat and said connecting section are integrated and inseparable, said connecting section being pliable and bendable to allow said cap to move relative to said bottom seat for opening and closing.